


## Standard Strap Type – PCV Series UV Resistant - Black

Manufactured from tough, durable Nylon 6/6 with carbon added for UV resistance

| Part Number     | Length L mm | Width W mm | Bundle Max. Diameter | Min. Tensile Strength Kg |
|-----------------|-------------|------------|----------------------|--------------------------|
| 15-PCV060/2.4W  | 64          | 2.4        | 11                   | 8                        |
| 15-PCV075/1.6W  | 75          | 1.6        | 15                   | 8                        |
| 15-PCV100/2.5W  | 100         | 2.5        | 22                   | 8                        |
| 15-PCV200/2.5W  | 203         | 2.5        | 55                   | 8                        |
| 15-PCV200/3.6W  | 203         | 3.6        | 52                   | 18                       |
| 15-PCV200/4.6W  | 203         | 4.6        | 52                   | 22                       |
| 15-PCV200/4.8W  | 203         | 4.8        | 52                   | 22                       |
| 15-PCV200/7.6W  | 203         | 7.6        | 52                   | 55                       |
| 15-PCV250/3.6W  | 250         | 3.6        | 68                   | 18                       |
| 15-PCV250/4.8W  | 250         | 4.8        | 68                   | 22                       |
| 15-PCV292/3.6W  | 292         | 3.6        | 82                   | 18                       |
| 15-PCV300/4.8W  | 300         | 4.8        | 83                   | 22                       |
| 15-PCV340/7.6W  | 340         | 7.6        | 92                   | 55                       |
| 15-PCV370/4.8W  | 368         | 4.8        | 105                  | 34                       |
| 15-PCV380/8.0W  | 380         | 8.0        | 105                  | 60                       |
| 15-PCV432/4.8W  | 432         | 4.8        | 125                  | 22                       |
| 15-PCV450/8.0W  | 450         | 8.0        | 128                  | 55                       |
| 15-PCV500/4.8W  | 500         | 4.8        | 147                  | 22                       |
| 15-PCV610/4.8W  | 610         | 4.8        | 181                  | 22                       |
| 15-PCV610/9.0W  | 610         | 9.0        | 177                  | 80                       |
| 15-PCV635/4.8W  | 635         | 4.8        | 189                  | 22                       |
| 15-PCV914/4.8W  | 914         | 4.8        | 278                  | 22                       |
| 15-PCV914/9.0W  | 914         | 9.0        | 275                  | 80                       |
| 15-PCV1500/9.0W | 1500        | 9.0        | 462                  | 80                       |



Material: UV Resistant Black Nylon 6/6

## Releasable Cable Ties

Easy finger catch good for temporary fastening

| Part Number     | Length L mm | Width W mm | Bundle Max. Diameter | Min. Tensile Strength Kg | Colour  |
|-----------------|-------------|------------|----------------------|--------------------------|---------|
| 15-PCR100/3.6   | 100         | 3.6        | 25                   | 18                       | Natural |
| 15-PCR125/4.5B  | 125         | 4.5        | 25                   | 22                       | Black   |
| 15-PCR125/7.6BX | 125         | 7.6        | 30                   | 22                       | Black   |
| 15-PCR150/4.7   | 150         | 4.6        | 39                   | 22                       | Natural |
| 15-PCR200/4.5B  | 200         | 4.6        | 50                   | 22                       | Black   |
| 15-PCR200/4.7   | 200         | 4.6        | 50                   | 22                       | Natural |
| 15-PCR200/7.6   | 200         | 7.6        | 50                   | 22                       | Natural |
| 15-PCR300/7.6B  | 300         | 7.6        | 89                   | 22                       | Black   |
| 15-PCR200/7.6BX | 200         | 7.6        | 50                   | 22                       | Black   |
| 15-PCR300/4.5   | 300         | 4.5        | 80                   | 22                       | Natural |
| 15-PCR300/4.5B  | 300         | 4.5        | 80                   | 22                       | Black   |
| 15-PCR370/4.8   | 370         | 4.8        | 102                  | 22                       | Natural |
| 15-PCR590/12.8L | 590         | 12.8       | 170                  | 114                      | Natural |



Material: UL Approved Nylon 6/6

