

Cable Entry Caps / Desk Grommets

Features a smooth design for desktop mounting

Part Number	Outside Diameter	Colour
14-DGB60	60mm	Black
14-DGG60	60mm	Grey
14-DGW60	60mm	White

Other colours available to order.





Insulating Bushes - Miniature

Insulate wires and cables from raw edges • Snaps quickly into panel hole • Accomodate panels up to 1.6mm thick

Requires internal clearance of only 3.2mm.

Temperature Index 105°C.

Part Number	Panel Hole Diameter	Max. Cable Diameter A	Overall Length C	Outside Diameter B
22-PPB05	4.8	3.2	6.2	6.4
22-PPB08	8.0	6.4	6.2	9.5
22-PPB12	11.9	8.8	6.4	13.5
22-PPB13	12.7	9.5	6.4	14.3
22-PPB14	13.5	10.3	6.4	15.2
22-PPB16	15.9	12.7	6.4	17.9
22-PPB19	19.0	16.0	6.4	21.0
22-PPB22	22.2	19.0	6.4	23.8



Material: Black Heat Stabilized Nylon 6/6 UL94V2


Insulating Bushes - Standard

Standard bushes have multiple locks which snap positively into panels ranging from 0.8 to 3.2 mm thick

Meets UL & CSA Temperature and Pull-out tests.

Temperature Index 105°C.

Part Number	Panel Hole Diameter	Max. Cable Diameter A	Overall Length C	Outside Diameter B	Max. Panel Thickness
22-PLB06	6.3	3.2	8.0	8.0	1.6
22-PLB08	8.0	4.8	8.0	9.5	1.6
22-PLB09	9.5	6.3	10.3	11.9	3.2
22-PLB09X	9.5	4.8	10.3	11.9	3.2
22-PLB11	11.1	8.0	10.3	13.5	3.2
22-PLB13	12.7	8.0	10.3	14.7	3.2
22-PLB13X	12.7	9.5	10.3	14.7	3.2
22-PLB14	14.3	8.0	10.3	16.7	3.2
22-PLB16	15.9	12.7	10.3	18.2	3.2
22-PLB19	19.1	15.9	10.3	21.4	3.2
22-PLB22	22.2	17.4	11.5	24.2	3.2
22-PLB25	25.4	19.0	11.5	28.6	3.2
22-PLB28	27.8	23.8	11.5	30.9	3.2
22-PLB30	30.2	23.8	11.5	33.3	3.2
22-PLB32	31.7	23.8	11.5	34.5	3.2
22-PLB35	34.9	25.4	11.5	37.3	3.2
22-PLB38	38.1	33.3	11.5	40.9	3.2
22-PLB38X	38.1	28.6	11.5	40.9	3.2
22-PLB44	44.4	34.9	11.5	47.6	3.2
22-PLB50	50.8	41.2	11.5	54.0	3.2
22-PLB57	57.1	44.5	18.3	63.0	6.4
22-PLB63	63.5	49.9	18.4	68.5	6.4
22-PLB76	76.2	62.7	18.3	80.2	6.4
22-PLB85	85.7	71.4	18.3	92.9	6.4
22-PLB89	88.9	74.6	18.3	92.9	6.4
22-PLB101	101.6	87.8	18.3	105.9	6.4



Material: Black Heat Stabilized Nylon 6/6 UL94V2

Some sizes available in white.